

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Draiad	ŀ •
Project	ι.

Model #: Item # :

Qty :

Available W/H :

Approval :

Glass Door Refrigerator

____ FEATURES & BENEFITS =___

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Digital temperature control & monitor system

- · Keep food products safe by maintaining constant temperatures. · Alarms that sound when doors are not sealed shut; protect against food spoilage that originates from cold air leaks.
- · Early warning alarm program detects issues before malfunction occurs.
- · Digital display allows for easy monitoring.
- · Programs interpret the condition of refrigeration systems by self-diagnosis.
- · Rapid cool-down functions (Turbo cooling).
- · Automatic evaporator fan motor delays.

Hydrocarbon refrigerants (R-600a)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet the new standards of the EPA and DOE in 2017. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Stainless steel interior & exterior

The Turbo Air Super Deluxe glass door model is constructed with stainless steel exterior. The door is glass with AL frame. The interior is stainless steel that guarantees the utmost in cleanliness and long product life. The Super Deluxe adds a touch of style to the most refined setting.

Double pane glass doors with Low-E glass

Energy saving double pane glass doors are equipped with Low-emissivity glass, which reduces outer heat gain and decreases energy consumption. It enhances energy efficiency and minimizes condensation. Lightweight door construction also reduces door maintenance and bushing wear, which in turn facilitates smoother door opening.

High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- Ergonomically designed doors Customers' fatigue fades away with easy grip handles and doors that open effortlessly. Self-closing features make this the ultimate choice in customer convenience.
- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- LED interior lighting
- Bottom mount compressor



Model: TSR-23GSD-N6



Refrigerator holds 33°F ~ 38°F for the best in food preservation



AND CO.

					Refrigerant Some		VEAR WARRANTY ULLAGY ULLAGY LAND
Model	Swing Door	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	$L x D^* x H^+$ (inches)
TSR-23GSD-N6	1	20	3	1/5	1.6	310	27 x 303/8x 781/4

* Depth does not include 1-1/2" for glass door handles. † Height does not include 5" caster height or 6" optional legs

Glass Door Refrigerator

Model: TSR-23GSD-N6

ELECTRICAL DATA					
Voltage	115/60/1				
Plug Type	() NEMA-5-15P				
Full Load Amperes	1.6				
Compressor HP	1/5				
Feed Wires with Ground	3				
Cord Length (ft.)	7				
Refrigerant	R-600 a				
DIMENSIONAL DATA					
# of Doors	1				
# of Racks Accepted	1				
Net Capacity (cu. ft.)	20				
Ext. Length Overall (in.)	27 (686mm)				
Ext. Depth Overall (in.)*	303/8 (772mm)				
Ext. Height Overall (in.) [†]	781/4 (1987mm)				
Int. Length Overall (in.)	23 (584mm)				
Int. Depth Overall (in.)	261/4 (666mm)				
Int. Height Overall (in.)	60 (1524mm)				
Gross Weight (lbs.)	310				
# of Shelves	3				
Shelf Size (L x D) (in.)	22 x 231/2				

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 1-1/2" for glass door handles.

† Height does not include 5" caster height or 6" optional legs.

WARRANTY: 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor

- Anti-corrosion coated evaporator
- Easy replaceable one piece magnetic door gaskets
- Self-contained system
- Solid and sturdy grille design
- Door locks standard
- Standard 4" dia. swivel casters with locks on the front set
- Legs available (optional)

OPTIONAL ACCESSORIES :

- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- G" stainless steel leg: 30221M0600
- Additional PE coated wire shelf: 30278L0300

PLAN VIEW

(unit : inch)





SIDE VIEW

Ver.20171026



(GEAMAN

- **Turbo Air** : 800-627-0032 **GK** : 800-500-3519
- Warranty : 800-381-7770 AC : 888-900-1002







