

## ESG35T High Efficiency Value Gas Fryer

Model



### Specifications

# Value, high-efficiency frying at its best. Designed for all-purpose value frying usage.

Frymaster has a whole new category of fryers, "Value High-Efficiency". The new ESG35T is a value fryer that exceeds ENERGY STAR guidelines and gualifies for energy saving rebates. The ESG35T requires only 70,000 BTU/hr, 33% less than comparable standard models. The 6" heating tubes have proprietary baffles and painted interiors that deliver super heat transfer. This reduces flue heat loss by 27%. The insulated frypot allows for a low idle rate of 6,143 Btu/hr. further enhancing the energy savings provided by the ESG35T. And, this 35-lb fryer has the same cooking capacity as a 45-lb fryer, saving 10 lbs. of oil every time the frypot is filled. The innovative ESG35T has a wide cold zone keeping crumbs and sediment away from

the cooking area, keeping oil fresh longer. In addition, the frypot bottom slopes to the front so that the oil, sediment and crumbs can be easily flushed out of the pot.

Project.

Approval\_ Date \_\_\_\_

Item \_\_\_\_\_Quantity\_\_\_\_\_CSI Section 11400

Prompt recovery is assured with a durable temperature probe; no electrical hook-up is required for the millivolt control system.

Frymaster's ESG35T is a value fryer that reduces operating costs by saving energy and oil use. It also reduces the cost of ownership by qualifying for energy savings rebates.









8700 Line Avenue Shreveport, LA 71106 USA Tel: 318-865-1711 Tel: 1-800-221-4583 Fax: 318-868-5987 E-mail: info@frymaster.com www.frymaster.com Bulletin No. 818-0749 Revised 2/1/16 Litho in U.S.A. ©Frymaster







#### DIMENSIONS

		OVERALL SIZE (cm)			DRAIN		APPROXIMATE SHIPPING DIMENSIONS					
MODEL	OIL CAPACITY	WIDTH	DEPTH	HEIGHT	VALVE HEIGHT (cm)	NO. OF TUBES	WEIGHT	CLASS	CU. FT.	DIMENSIONS (cm)		5
ESG35T	35 lbs. (17 liter)	15-1/2″ (39.4)	29-1/8″ (74)	44″ (111.8)	16-1/2″ (42)	3	165 (75 kg)	85	22	<b>W</b> 22″ (56)	<b>D</b> 36″ (91)	<b>H</b> 47″ (119)

#### POWER REQUIREMENTS

MODEL	NATURAL GAS	LP GAS	GAS	ELECTRICAL	
	INPUT RATING	INPUT RATING	CONNECTION	REQUIREMENT	
ESG35T	70,000 Btu/hr. (17,632 kcal) (20.5 kw)	67,000 Btu/hr. (16,877 kcal) (19.6 kw)	3/4" N.P.T. Regulator not required for manifold pressure. See note <sup>*</sup> .	NONE	

#### HOW TO SPECIFY

The following description will assist with ordering the features desired for this equipment:

ESG35T 35-lb (17-liter) tube-type gas fryer with millivolt controller, and durable temperature probe; meets ENERGY STAR® guidelines.

#### ORDERING DATA

Please specify: Natural or propane gas Altitude -- if above 2000 ft. (610 m)

#### NOTE:

DO NOT CURB MOUNT. \*SUPPLY PRESSURE: DO NOT EXCEED 14" W.C. or 1/2 PSI. No warranty for mobile kitchen applications.

8700 Line Avenue

Shreveport, LA 71106 USA Tel: 318-865-1711 Tel: 1-800-221-4583

Fax: 318-868-5987 E-mail: info@frvmaster.com www.frymaster.com Bulletin No. 818-0749 Revised 2/1/16

Litho in U.S.A. ©Frymaster



Model #\_\_\_\_\_ CSI Section 11400